

Publish Date : 10.07.2019 | Rev no: 01

1U - Sliding Fiber Enclosure Tray - With SC Plates

DINTEK Light-LINKS™ 1U rack mount fiber optic splice and termination enclosures provide an economical and quality solution for installations of any size, where direct termination or pigtail splicing is required.

The typical use of these enclosures include situations where outside plant cables are terminated onto the back of the adapter plate or where pigtails are spliced onto the incoming cable. These enclosures are also used as point to point patch connections or as end termination for backbone spurs in the Telecom environment.

The Light-LINKS™ 1U, 2U and 4U fiber optic enclosure range comes in two designs, sliding and fixed type. The units can be purchased as a base unit without adapter plates or with adapter plates included depending upon the customers preference.



Features

- Designed for fiber optical backbone cabling applications.
- Snap-in adapter plates & removable cover, provide for easy access and installation.
- Fixed type & Sliding type enclosure option available
- Easily added to existing multimedia installations that will require fiber terminations.
- Splice tray, sleeves and LC, SC, ST adapters are available separately to load into the enclosure.(optional)
- 1U Size give up to 24 or 48 depending on adapter type
- 2U Size give up to 48 or 96 depending on adapter type

Standards

- Standards ISO/IEC 11801
- Cenelec EN 50173-1 / TIA-568 C.0
- Data Center Cenelec EN 50173-5
- ISO/IEC 24764/ TIA-942

Dimensions

- Per 19" rack mounts requirements.
- Material: Iron - Powder Coated Black
- Dimensions: 1U - h 44mm x w 482mm x d 300mm
2U - h 88mm x w 482mm x d 300mm



Ordering Information

Product Number	Product Name	Accepted Modules	Splice Tray	Std Ctn Qty
2201-24059	1U - Sliding Fiber Enclosure Tray	2 X 6 port Duplex SC plates	Yes	4
2201-24063	1U - Sliding Fiber Enclosure Tray	2 X 12 port Duplex LC plates	Yes	4
2201-24064	1U - Sliding Fiber Enclosure Tray	2 X 12 port Simplex ST plates	Yes	4