



Datasheet 2107-12001

Publish Date: 23.10.2022 | Rev no: 17

LC Male to SC Female UPC Simplex Singlemode Adapter

The DINTEK Light-LINKS[™] LC (Male) - SC (Female) UPC Fiber Optic Adapter is a premium style fiber optic adapter that allows for the precision connection of differing fiber optic connector types including different ferrule size. It is designed to incorporate the SC into the LC environment. The compact design allows for space saving and enables network operators to reduce costs by eliminating hybrid cable assemblies.

A fiber optic adapter, which is also called a fiber coupler, is a single device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines.



Features

- Low Insertion Loss ≤0.5dB (Average)
- Zirconia Ceramic Sleeve
- High-precision fiber alignment
- Easy clip-in installation via stainless steel clips
- Complete with dust-eliminating cap for a clean interior environment
- Available in alternative of connector types

Standards Compliance

- Standards ISO/IEC 11801
- Cenelec EN 50173-1 / TIA-568 C.0
- Data Center Cenelec EN 50173-5
- ISO/IEC 24764/ TIA-942
- Ethernet IEEE 802.3; 10/40/100GbE

Applications

- Testing instruments
- Telecommunications
- CATV
- Local area networks



Technical Properties				
Fiber Type	Singlemode			
Ferrule Profile	UPC			
Insertion/withdrawal cycles	≤ 500			
Connection Configuration	SC (Female) - LC (Male)			
Degree of protection	IP20			
Housing material	Plastic / Stainless Steel			
Insertion Loss	≤0.5dB			

Ordering Information					
Product Number	Product Name	Configuration	Mode Type	Polish Type	
2107-12001	LC Male to SC Female Simplex Singlemode Adapter	Simplex	Singlemode	UPC	

DINTEK Electronic Limited

台北市中山區中山北路二段96號 嘉新第二大樓五樓N511 N511, 5F, 2nd Bldg, No. 96, Sec. 2, Zhongshan N. Rd.Zhongshan Dist., Taipei City 10449, Taiwan P: +886-2-25223138 **E-mail:** sales@dintek.com.tw **W:** www.dintek.com.tw